# ORDINANCE NO. 2015-007

# FLOODPLAIN ORDINANCE

AN ORDINANCE OF HILLTOWN TOWNSHIP REQUIRING ALL PERSONS, PARTNERSHIPS, BUSINESSES, AND CORPORATIONS TO OBTAIN A PERMIT FOR ANY CONSTRUCTION OR DEVELOPMENT WITH A FLOODPLAIN; PROVIDING FOR THE ISSUANCE OF SUCH PERMITS; SETTING FORTH CERTAIN MINIMUM REQUIREMENTS FOR CONSTRUCTION AND DEVELOPMENT WITHIN AREAS OF HILLTOWN TOWNSHIP WHICH ARE SUBJECT TO FLOODING; AND ESTABLISHING PENALTIES FOR ANY PERSONS WHO FAIL, OR REFUSES TO COMPLY WITH, THE REQUIREMENTS OF THIS ORDINANCE.

#### ARTICLE I. STATUTORY AUTHORIZATION

The legislature of the Commonwealth of Pennsylvania has, by the passage of the Pennsylvania Floodplain Management Act of 1978, delegated the responsibility to local governmental units to adopt floodplain management regulations to promote public health, safety, and the general welfare of its citizenry. Therefore, the Board of Supervisors of Hilltown Township does hereby order as fo lows:

## **ARTICLE II. GENERAL PROVISIONS**

### Section 2.01 Intent

The intent of this Ordinance is to:

- A. Promote the general health, welfare, and safety of the community.
- B. Encourage the utilization of appropriate construction practices in order to prevent or minimize flood damage in the future.
- C. Minimize danger to public health by protecting water supply and natural drainage.
- D. Reduce financial burdens imposed on the community, its governmental units, and its residents, by preventing excessive development in areas subject to flooding.
- E. Comply with federal and state floodplain management requirements.

### Section 2.02 Applicability

- A. It shall be unlawful for any person, partnership, business or corporation to undertake, or cause to be undertaken, any construction or development anywhere within an Identified Floodplain Area within Hilltown Township unless a Floodplain Permit has been obtained from the Floodplain Administrator.
- B. A Floodplain Permit shall not be required for minor repairs to existing buildings or structures.

### Section 2.03 Abrogation and Greater Restrictions

This ordinance supersedes any other conflicting provisions which may be in effect in identified floodplain areas. However, any other ordinance provisions shall remain in full force and effect to the extent that those provisions are more restrictive. If there is any conflict between any of the provisions of this Ordinance, the more restrictive shall apply.

# Section 2.04 Severability

If any section, subsection, paragraph, sentence, clause, or phrase of this Ordinance shall be declared invalid for any reason whatsoever, such a decision shall not affect the remaining portions of the Ordinance, which shall remain in full force and effect, and for this purpose the provisions of this Ordinance are hereby declared to be severable.

### Section 2.05 Warning and Disclaimer of Liability

The degree of flood protection sought by the provisions of this Ordinance is considered reasonable for regulatory purposes and is based on acceptable engineering methods of study. Larger floods may occur or flood heights may be increased by man-made or natural causes, such as dams, ice jams and bridge openings restricted by debris. This Ordinance does not imply that areas outside any identified floodplain areas, or that land uses permitted within such areas will be free from flooding or flood damages.

This Ordinance shall not create liability on the part of the Township or any officer or employee thereof for any flood damages that result from reliance on this Ordinance or any administrative decision lawfully made there under.

#### ARTICLE III. ADMINISTRATION

### Section 3.01 Designation of the Floodplain Administrator

The Board of Supervisors shall annually appoint the Township Engineer as the Floodplain Administrator to administer and enforce this Ordinance and is referred to herein as the Floodplain Administrator.

In the absence of a designated Floodplain Administrator, the Floodplain Administrator duties are to be fulfilled by the Township Manager.

### Section 3.02 Permits Required

A Floodplain Permit shall be required before any construction or development is undertaken within any identified Floodplain Area of Hilltown Township.

### Section 3.03 Duties and Responsibilities of Floodplain Administrator

- A. The Floodplain Administrator shall issue a Permit only after it has been determined that the proposed work to be undertaken will be in conformance with the requirements of this and all other applicable codes and ordinances.
- B. Prior to the issuance of any permit, the Floodplain Administrator shall review the application for the permit to determine if all other necessary government permits required by state and federal laws have been obtained, such as those required by the Pennsylvania

Sewage Facilities Act (Act 1966-537, as amended); the Pennsylvania Dam Safety and Encroachments Act (Act 1978-325, as amended); the Pennsylvania Clean Streams Act (Act 1937-394, as amended); and the U.S. Clean Water Act, Section 404, 33, U.S.C. 1344. No permit shall be issued until this determination has been made.

- C. During the construction period, the Floodplain Administrator or other authorized official shall inspect the premises to determine that the work is progressing in compliance with the information provided on the permit application and with all applicable municipal laws and ordinances. He/she shall make as many inspections during and upon completion of the work as are deemed necessary.
- D. In the discharge of his/her duties, the Floodplain Administrator shall have the authority to enter any building, structure, premises or development in the identified floodplain area, upon presentation of proper credentials, at any reasonable hour to enforce the provisions of this ordinance.
- In the event the Floodplain Administrator discovers that the work does not comply with the permit application or any applicable laws and ordinances, or that there has been a false statement or misrepresentation by any applicant, the Floodplain Administrator shall revoke the Permit and report such fact to the Board of Supervisors for whatever action the Board of Supervisors considers necessary.
- F. The Floodplain Administrator shall maintain in perpetuity all records associated with the requirements of this ordinance including, but not limited to, finished construction elevation data, permitting, inspection and enforcement.
- G. The Floodplain Administrator is the official responsible for submitting a biennial report to FEMA concerning community participation in the National Flood Insurance Program.
- H. The responsibility, authority and means to implement the commitments of the Floodplain Administrator can be delegated from the person identified. However, the ultimate responsibility lies with the person identified in the Floodplain Ordinance as the floodplain administrator/manager.
- I. The Floodplain Administrator shall consider the requirements of the 34 PA Code and the 2009 IBC and the 2009 IRC or latest revisions thereof.

### Section 3.04 Application Procedures and Requirements

- A. Application for a Floodplain Permit shall be made, in writing, to the Floodplain Administrator on forms supplied by the Township. The application shall contain the following:
  - Name and address of applicant.
  - 2. Name and address of owner of land on which proposed construction is to occur.
  - 3. Name and address of contractor.
  - 4. Site location including address and tax map parcel number.
  - 5. Listing of other permits required.

- 6. Brief description of proposed work and estimated cost, including a breakout of flood-related cost and the market value of the building before the flood damage occurred where appropriate.
- 7. A plan of the site showing the exact size and location of the proposed construction as well as any existing buildings or structures.
- B. If any proposed construction or development is located entirely or partially within any identified floodplain area, applicants for a Floodplain Permits shall provide all the necessary information in sufficient detail and clarity to enable the Floodplain Administrator to determine that:
  - 1. all such proposals are consistent with the need to minimize flood damage and conform with the requirements of this and all other applicable codes and ordinances:
  - 2. all utilities and facilities, such as sewer, gas, electrical and water systems are located and constructed to minimize or eliminate flood damage;
  - 3. adequate drainage is provided so as to reduce exposure to flood hazards;
  - 4. structures will be anchored to prevent floatation, collapse, or lateral movement;
  - 5. building materials are flood-resistant;
  - 6. appropriate practices that minimize flood damage have been used; and
  - 7. electrical, heating, ventilation, plumbing, air conditioning equipment, and other service facilities have been designed and located to prevent water entry or accumulation.
- C. Applicants shall file the following minimum information plus any other pertinent information as may be required by the Floodplain Administrator to make the above determination:
  - 1. A completed Floodplain Permit Application Form.
  - 2. A plan of the entire site, clearly and legibly drawn at a scale of one (1) inch being equal to one hundred (100) feet or less, showing the following:
    - a. north arrow, scale, and date;
    - b. topographic contour lines, if available;
    - c. all property and lot lines including dimensions, and the size of the site expressed in acres or square feet;
    - d. location of all existing and proposed buildings, structures, and other improvements, including the location of any existing or proposed subdivision and land development;
    - e. location of all existing streets, drives, and other access ways; and

- f. location of any existing bodies of water or watercourses, identified floodplain areas, and, if available, information pertaining to the floodway, and the flow of water including direction and velocities.
- 3. Plans of all proposed buildings, structures and other improvements, drawn at suitable scale showing the following:
  - a. proposed lowest floor elevation of any proposed building based upon North American Vertical Datum of 1988:
  - b. elevation of the base flood; and
  - c. supplemental information as may be necessary under 34 PA Code, the 2009 IBC or the 2009 IRC.
- 4. The following data and documentation:
  - a. if available, information concerning flood depths, pressures, velocities, impact and uplift forces and other factors associated with a base flood;
  - detailed information concerning any proposed floodproofing measures and corresponding elevations;
  - c. if available, information concerning flood depths, pressures, velocities, impact and uplift forces and other factors associated with a base flood; and Floodway Area (See section 4.02 A) when combined with all other existing and anticipated development, will not increase the base flood elevation at any point.
  - d. a document, certified by a registered professional engineer or architect, which states that the proposed construction or development has been adequately designed to withstand the pressures, velocities, impact and uplift forces associated with the base flood.
    - Such statement shall include a description of the type and extent of flood proofing measures which have been incorporated into the design of the structure or the development;
  - detailed information needed to determine compliance with Section 5.03F., Storage, and Section 5.04, Development Which May Endanger Human Life, including:
    - (1) the amount, location and purpose of any materials or substances referred to in Sections 5.03 F and 5.04 which are intended to be used, produced, stored or otherwise maintained on site.
    - (2) a description of the safeguards incorporated into the design of the proposed structure to prevent leaks or spills of the dangerous materials or substances listed in Section 5.04 during a base flood.
  - f. the appropriate component of the Department of Environmental Protection's "Planning Module for Land Development"; and

g. where any excavation or grading is proposed, a plan meeting the requirements of the Department of Environmental Protection, to implement and maintain erosion and sedimentation control.

### Section 3.05 Review by County Conservation District

A copy of all applications and plans for any proposed construction or development with a proposed earth disturbance of 1000 square feet or more in any identified floodplain area shall be submitted by the applicant to the Bucks County Conservation District for review. Requirements of the Bucks County Conservation District shall be incorporated by the applicant into the proposed plan. Prior to the issuance of a Floodplain Permit by the Township, a "letter of adequacy" must be received from Bucks County Conservation District, where applicable.

### Section 3.06 Review of Application by Others

A copy of all plans and applications for any proposed construction or development in any identified floodplain area to be considered for approval may be submitted by the Floodplain Administrator to any other appropriate agencies or individuals (e.g. Zoning Officer, Planning Commission, etc.) for review and comment.

## Section 3.07 Changes

After the issuance of a Floodplain Permit by the Floodplain Administrator, no changes of any kind shall be made to the application, permit or any of the plans, specifications or other documents submitted with the application without the written consent or approval of the Floodplain Administrator. Requests for any such change shall be in writing, and shall be submitted by the applicant to Floodplain Administrator for consideration.

# Section 3.08 Placards

In addition to the Floodplain Permit, the Floodplain Administrator shall issue a placard which shall be displayed on the premises during the time construction is in progress. This placard shall show the number of the Floodplain Permit and the date of its issuance, and be signed by the Floodplain Administrator.

#### Section 3.09 Start of Construction

Work on the proposed construction and/or development shall begin within 180 days after the date of issuance and shall be completed within twelve (12) months after the date of issuance of the Floodplain Permit or the permit shall expire unless a time extension is granted, in writing, by the Floodplain Administrator.

The actual start of construction means either the first placement of permanent construction of a structure on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufacture home on a foundation. Permanent construction does not include land preparation, such as clearing, grading, and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for basement, footings, piers, or foundations or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. For a substantial improvement, the actual start of construction means the first,

alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

Time extensions shall be granted only if a written request is submitted by the applicant, which sets forth sufficient and reasonable cause for the Floodplain Administrator to approve such a request and the original permit is compliant with the Ordinance and FIRM/FIS in effect at the time the extension is granted.

### Section 3.10 Fees

Applicants for a Floodplain Permit shall, at the time of making application, pay to the Township, a fee in accordance with a Fee Schedule adopted by Resolution of the Board of Supervisors upon enactment of this Ordinance or as such schedule may be amended by Resolution of the Board of Supervisors.

### Section 3.11 Enforcement

#### A. Notices

Whenever the Floodplain Administrator or other authorized Township representative determines that there are reasonable grounds to believe that there has been a violation of any provisions of this Ordinance, or of any regulations adopted pursuant thereto, the Floodplain Administrator shall give notice of such alleged violation as hereinafter provided. Such notice shall:

- be in writing;
- 2. include a statement of the reasons for its issuance;
- 3. allow a reasonable time not to exceed a period of thirty (30) days for the performance of any act it requires;
- 4. be served upon the property owner or his agent as the case may require; provided, however, that such notice or order shall be deemed to have been properly served upon such owner or agent when a copy thereof has been served with such notice by any other method authorized or required by the laws of this State; and
- 5. contain an outline of remedial actions which, if taken, will effect compliance with the provisions of this Ordinance.

#### B. Penalties

Any person who fails to comply with any or all of the requirements or provisions of this Ordinance or who fails or refuses to comply with any notice, order or direction of the Floodplain Administrator or any other authorized employee of the Township shall be guilty of a summary offense and upon conviction shall pay a fine to Hilltown Township of not less than Twenty-five Dollars (\$25.00) nor more than Six Hundred Dollars (\$600.00) plus costs of prosecution. In addition to the above penalties all other actions are hereby reserved including an action in equity for the proper enforcement of this Ordinance. The imposition of a fine or penalty for any violation of, or noncompliance with, this Ordinance shall not excuse the violation or noncompliance or permit it to continue and all such persons shall be required to correct or remedy such violations and noncompliance within a reasonable

time. Any development initiated or any structure or building constructed, reconstructed, enlarged, altered, or relocated, in noncompliance with this Ordinance may be declared by the Board of Supervisors to be a public nuisance and abatable as such.

# Section 3.12 Appeals

- A. Any person aggrieved by any action or decision of the Floodplain Administrator concerning the administration of the provisions of this Ordinance, may appeal to the Zoning Hearing Board. Such appeal must be filed, in writing, within thirty (30) days after the decision, determination or action of the Floodplain Administrator.
- B. Upon receipt of such appeal the Zoning Hearing Board shall consider the appeal in accordance with the Municipalities Planning Code and any other local ordinance.
- C. Any person aggrieved by any decision of the Zoning Hearing Board may seek relief there from by appeal to court, as provided by the laws of this Commonwealth including the Pennsylvania Flood Plain Management Act.

#### ARTICLE IV. IDENTIFICATION OF FLOODPLAIN AREAS

## Section 4.01 Identification

The Identified Floodplain Area shall be:

- A. Any areas of Hilltown Township, classified as special flood hazard areas (SFHAs) in the Flood Insurance Study (FIS) and the accompanying Flood Insurance Rate Maps (FIRMs) dated March 16, 2015 and issued by the Federal Emergency Management Agency (FEMA) or the most recent revision thereof, including all digital data developed as part of the Flood Insurance Study and,
- B. For areas abutting streams and watercourses where the one hundred year floodplain (one percent [1%] annual chance flood) has not been delineated by a Flood Insurance Study, the applicant shall submit a floodplain identification study. The study prepared by a registered professional engineer expert in the preparation of hydrologic and hydraulic studies shall be used to delineate the one hundred year floodplain. The floodplain study shall be subject to the review and approval of the Township. All areas inundated by the one-hundred year flood shall be included in the Floodplain Area.

The above referenced FIS and FIRMs, and any subsequent revisions and amendments are hereby adopted by Hilltown Township and declared to be a part of this Ordinance.

# Section 4.02 Description and Special Requirements of Identified Floodplain Areas

The identified floodplain area shall consist of the following specific areas/districts:

A. The Floodway Area/District identified as floodway in the FIS which represents the channel of a watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without any increase in the water surface elevation at any point. This term shall also include floodway areas which have been identified in other available studies or sources of information for those special floodplain areas where no floodway has been identified in the FIS.

- 1. Within any floodway area, no encroachments, including fill, new construction, substantial improvements, or other development shall be permitted unless it has been demonstrated through hydrologic and hydraulic analysis performed in accordance with standard engineering practice that the proposed encroachment would not result in any increase in flood levels within the community during the occurrence of the base flood discharge.
- 2. No new construction or development shall be allowed, unless a permit is obtained from the Department of Environmental Protection Regional Office.
- B. The AE Area/District shall be those areas adjacent to the floodway and identified as an AE Zone on the FIRM included in the FIS prepared by FEMA for which base flood elevations have been provided.
- C. The A Area/District shall be those areas identified as an A Zone on the FIRM included in the FIS prepared by FEMA and for which no one-percent (1%) annual chance flood elevations have been provided. For these areas, elevation and floodway information from other Federal, State, or other acceptable source shall be used when available. Where other acceptable information is not available, the elevation shall be determined by hydrologic and hydraulic engineering techniques. Hydrologic and hydraulic analyses shall be undertaken only by registered professional engineers or others of demonstrated qualifications, who shall certify that the technical methods used correctly reflect currently accepted technical concepts. Studies, analyses, computations, etc., shall be submitted in sufficient detail to allow a thorough technical review by the Township.
- D. For areas adjoining streams, ponds, and lakes not included in the FIS prepared by FEMA, the applicant shall be required to determine the elevation and area of the floodplain with hydrologic and hydraulic engineering techniques. Hydrologic and hydraulic analyses shall be undertaken only by registered professional engineers or others of demonstrated qualifications, who shall certify that the technical methods used correctly reflect currently accepted technical concepts. Studies, analyses, computations, etc., shall be submitted in sufficient detail to allow a thorough technical review by the Township. All areas inundated by the one-hundred year flood shall be included in the Floodplain Area.
- E. In any identified floodplain area, no new construction or development, with the exception of stream crossings for utilities, roads or driveways where a permit is obtained from the Department of Environmental Protection Regional Office, shall be located within the area measured fifty (50) feet landward from the top-of-bank of any watercourse.

### Section 4.03 Changes in Identification of Area

The identified floodplain area may be revised or modified by the Board of Supervisors where studies or information provided by a qualified agency or person documents the need for such revision. However, prior to any such change within the A Area/District or AE Area/District, approval must be obtained from FEMA. Additionally, as soon as practicable, but not later than six (6) months after the date such information becomes available, FEMA shall be notified of the changes by submission of technical or scientific data. Refer Section 5.01 B for situations where FEMA notification is required.

### Section 4.04 Boundary Disputes

Should a dispute concerning any identified floodplain boundary arise, an initial determination shall be made by the Floodplain Administrator and any party aggrieved by this decision or determination may appeal to the Zoning Hearing Board. The burden of proof shall be on the appellant.

### Section 4.05 Jurisdictional Boundary Changes

Prior to development occurring in areas where annexation or other corporate boundary changes are proposed or have occurred, the Township shall review flood hazard data affecting the lands subject to boundary changes. The Township shall adopt and enforce floodplain regulations in areas subject to annexation or corporate boundary changes which meet or exceed those in CFR 44 60.3.

### ARTICLE V. TECHNICAL PROVISIONS

### Section 5.01 General

- A. Alteration or Relocation of Watercourse
  - No encroachment, alteration, or improvement of any kind shall be made to any
    watercourse until all adjacent municipalities which may be affected by such action
    have been notified by the Township, and until all required permits or approvals have
    been first obtained from the Department of Environmental Protection Regional Office.
  - 2. No encroachment, alteration, or improvement of any kind shall be made to any watercourse unless it can be shown that the activity will not reduce or impede the flood carrying capacity of the watercourse in any way.
  - 3. In addition, FEMA and Pennsylvania Department of Community and Economic Development shall be notified prior to any alteration or relocation of any watercourse included in the FIS.
- B. When a community proposes to permit the following encroachments:
  - Any development that causes a rise in the base flood elevations within the floodway, or
  - alteration or relocation of a stream including but not limited to installing culverts and bridges within Identified Floodplain A or AE Areas (Refer Section 4.02 B. and C.);

the applicant shall (as per 44 CFR Part 65.12);

- 1. apply to FEMA for conditional approval of such action prior to permitting the encroachments to occur.
- 2. Upon receipt of the Administrator's conditional approval of map change and prior to approving the proposed encroachments, a community shall provide evidence to FEMA of the adoption of floodplain management ordinances incorporating the increased base flood elevations and/or revised floodway reflecting the post-project condition.

- 3. Upon completion of the proposed encroachments, a community shall provide as-built certifications. FEMA will initiate a final map revision upon receipt of such certifications in accordance with 44 CFR Part 67.
- C. Any new construction, development, uses or activities allowed within any identified floodplain area shall be undertaken in strict compliance with the provisions contained in this Ordinance and any other applicable codes, ordinances and regulations.
- D. Within any Identified Floodplain Area (refer Section 4.02) no new construction or development shall be located within the area measured fifty (50) feet landward from the top-of-bank of any watercourse, except for roads, driveways and utility crossings where the appropriate permit is obtained from the Department of Environmental Protection Regional Office.

### Section 5.02 Elevation and Floodproofing Requirements

- A. Residential Structures when permitted as a variance by the Zoning Hearing Board:
  - 1. In AE Zones, any new construction or substantial improvement shall have the lowest floor (including basement) elevated to, or above, the regulatory flood elevation.
  - 2. In A Zones, where there are no base flood elevations specified on the FIRM, any new construction or substantial improvement shall have the lowest floor (including basement) elevated to, or above, the regulatory flood elevation determined in accordance with Section 4.02.C of this Ordinance.
  - 3. The design and construction standards and specifications contained in the 2009 International Building Code (IBC) and in the 2009 International Residential Code (IRC) or the most recent revisions thereof and ASCE 24 and 34 PA Code (Ordinances 401-405 as amended) shall be utilized, where they are more restrictive.
- B. Non-residential Structures when permitted as a variance by the Zoning Hearing Board:
  - 1. In AE Zones, any new construction or substantial improvement of a non-residential structure shall have the lowest floor (including basement) elevated to, or above, the regulatory flood elevation, <u>or</u> be designed and constructed so that the space enclosed below the regulatory flood elevation:
    - a. is floodproofed so that the structure is watertight with walls substantially impermeable to the passage of water, and
    - b. has structural components with the capability of resisting hydrostatic and hydrodynamic loads and effects of buoyancy, and
    - c. is certified by a registered professional/architect that the design and methods of construction meet requirements of Title 44, Section 60.3, Subpart A, Requirements for Floodplain Management Regulations.
  - 2. In A Zones, where there are no base flood elevations specified on the FIRM, any new construction or substantial improvement shall have the lowest floor (including

basement) elevated or floodproofed to, or above, the regulatory flood elevation determined in accordance with Section 4.02.C of this ordinance.

- 3. Any non-residential structure, or part thereof, made watertight below the regulatory flood elevation shall be floodproofed in accordance with the WI or W2 space classification standards contained in the publication titled "Flood-Proofing Regulations" published by the U.S. Army Corps of Engineers (June 1972, as amended March 1992) or with some other equivalent standard. All plans and specifications for such floodproofing shall be accompanied by a statement certified by a registered professional engineer or architect which states that the proposed design and methods of construction are in conformance with the above referenced standards.
- 4. The design and construction standards and specifications contained in the 2009 International Building Code (IBC) and in the 2009 International Residential Code (IRC) or the most recent revisions thereof and ASCE 24 and 34 PA Code (Ordinances 401-405 as amended) shall be utilized where they are more restrictive.

### C. Space below the lowest floor

- 1. Fully enclosed space below the lowest floor (excluding basements) which will be used solely for the parking of a vehicle, building access, or incidental storage in an area other than a basement, shall be designed and constructed to allow for the automatic entry and exit of flood waters for the purpose of equalizing hydrostatic forces on exterior walls. The term "fully enclosed space" also includes crawl spaces.
- 2. Designs for meeting this requirement must either be certified by a registered professional engineer or architect, or meet or exceed the following minimum criteria:
  - a. a minimum of two openings having a net total area of not less than one (1) square inch for every square foot of enclosed space.
  - b. the bottom of all openings shall be no higher than one (1) foot above grade.
  - c. openings may be equipped with screens, louvers, etc. or other coverings or devices provided that they permit the automatic entry and exit of floodwaters.

### D. Historic Structures

Historic structures undergoing repair or rehabilitation that would constitute a substantial improvement as defined in this Ordinance, must comply with all Ordinance requirements that do not preclude a structure's continued designation as a historic structure. Documentation that a specific Ordinance requirement will cause removal of the structure from the National Register of Historic Place or the State Inventory of Historic Places must be obtained from the Secretary of the Interior or the State Historic Preservation Officer. Any exemption from Ordinance requirements will be the minimum necessary to preserve the historic character and design of the structure.

### E. Accessory structures

Structures accessory to a principal building need not be elevated or floodproofed to remain dry, but shall comply, at a minimum, with the following requirements:

- 1. the structure shall not be designed or used for human habitation, but shall be limited to the parking of vehicles, or to the storage of tools, material, and equipment related to the principal use or activity; and
- 2. floor area shall not exceed 200 square feet; and
- 3. the structure will have a low damage potential; and
- 4. the structure will be located on the site so as to cause the least obstruction to the flow of flood waters; and
- 5. power lines, wiring, and outlets will be elevated to at least one and one-half (1½) feet above the regulatory flood elevation; and
- 6. permanently affixed utility equipment and appliances such as furnaces, heaters, washers, dryers, etc. are prohibited; and
- 7. sanitary facilities are prohibited; and
- 8. the structure shall be adequately anchored to prevent flotation, lateral movement and collapse and shall be designed to automatically provide for the entry and exit of floodwater for the purpose of equalizing hydrostatic forces on the walls. Designs for meeting this requirement must either be certified by a registered professional engineer or architect, or meet or exceed the following minimum criteria:
  - a. a minimum of two openings having a net total area of not less than one (1) square inch for every square foot of enclosed space.
  - b. the bottom of all openings shall be no higher than one (1) foot above grade.
  - c. openings may be equipped with screens, louvers, etc. or other coverings or devices provided that they permit the automatic entry and exit of flood waters.

### Section 5.03 Design and Construction Standards

The following minimum standards shall apply for all construction and development proposed within any identified floodplain area:

#### A. Fill

Within any designated floodplain area, the use of fill shall be prohibited. If a variance is obtained in accordance with the criteria in Article VIII, fill shall:

- 1. extend laterally at least fifteen (15) feet beyond the building line from all points;
- 2. consist of soil or small rock materials only sanitary landfills shall not be permitted;
- 3. be compacted to provide necessary permeability and resistance to erosion, scouring, or settling;

- 4. be no steeper than one (1) vertical to three (3) horizontal feet unless substantiated data justifying steeper slopes are submitted to, and approved by the Floodplain Administrator; and
- 5. be used to the extent to which it does not adversely affect adjacent properties.

#### B. Drainage Facilities

Storm drainage facilities shall be designed to convey the flow of stormwater runoff in a safe and efficient manner. The system shall insure proper drainage along streets, and provide positive drainage away from buildings. The system shall also be designed to prevent the discharge of excess runoff onto adjacent properties.

# C. Water and Sanitary Sewer Facilities and Systems

- All new or replacement water supply and sanitary sewer facilities and systems shall be located, designed and constructed to minimize or eliminate flood damages and the infiltration of flood waters.
- 2. Sanitary sewer facilities and systems shall be designed to prevent the discharge of untreated sewage into flood waters.
- 3. No part of any on-site waste disposal system shall be located within any identified floodplain area except in strict compliance with all State and local regulations for such systems. If any such system is permitted, it shall be located so as to avoid impairment to it, or contamination from it, during a flood.
- 4. The design and construction provisions of the UCC and FEMA #348, "Protecting Building Utilities From Flood Damages" and the "International Private Sewage Disposal Code" shall be utilized.

# D. Other Utilities

All other utilities such as gas lines, electrical and telephone systems shall be located, elevated (where possible) and constructed to minimize the chance of impairment during a flood.

#### E. Streets

The finished elevation of all new streets shall be no less than one (1) foot below the regulatory flood elevation.

#### F. Storage

All materials that are buoyant, flammable, explosive, or in times of flooding, could be injurious to human, animal, or plant life, and not listed in Section 5.04, Development Which May Endanger Human Life, shall be stored at or above the regulatory flood elevation or flood proofed to the maximum extent possible.

### G. Placement of Buildings and Structures

All buildings and structures shall be designed, located, and constructed so as to offer the minimum obstruction to the flow of water and shall be designed to have a minimum effect upon the flow and height of flood water.

### H. Anchoring

- 1. All buildings and structures shall be firmly anchored in accordance with accepted engineering practices to prevent flotation, collapse, or lateral movement.
- 2. All air ducts, large pipes, storage tanks, and other similar objects or components located below the regulatory flood elevation shall be securely anchored or affixed to prevent flotation and waterproofed.

### I. Floors, Walls and Ceilings

- 1. Wood flooring used at or below the regulatory flood elevation shall be installed to accommodate a lateral expansion of the flooring, perpendicular to the flooring grain without causing structural damage to the building.
- 2. Plywood used at or below the regulatory flood elevation shall be of a "marine" or "water-resistant" variety.
- 3. Walls and ceilings at or below the regulatory flood elevation shall be designed and constructed of materials that are "water-resistant" and will withstand inundation
- 4. Windows, doors, and other components at or below the regulatory flood elevation shall be made of metal or other "water-resistant" material.

### J. Paints and Adhesives

- 1. Paints and other finishes used at or below the regulatory flood elevation shall be of "marine" or "water-resistant" quality.
- 2. Adhesives used at or below the regulatory flood elevation shall be of a "marine" or "water-resistant" variety.
- 3. All wooden components (doors, trim, cabinets, etc.) used at or below the regulatory flood elevation shall be finished with a "marine" or "water-resistant" paint or other finishing material.

### K. Electrical Components

- 1. Electrical distribution panels shall be at least three (3) feet above the base flood elevation.
- 2. Separate electrical circuits shall serve lower levels and shall be dropped from above.

### L. Equipment

Water heaters, furnaces, air conditioning and ventilating units, and other electrical, mechanical or utility equipment or apparatus shall not be located below the regulatory flood elevation.

### M. Fuel Supply Systems

All gas and oil supply systems shall be designed to prevent the infiltration of flood waters into the system and discharges from the system into flood waters. Additional provisions shall be made for the drainage of these systems in the event that flood water infiltration occurs.

#### N. Uniform Construction Code Coordination

The Standards and Specifications contained in 34 PA Code (Ordinances 401-405), as amended and not limited to the following provisions shall apply to the above and other sections and sub-sections of this ordinance, to the extent that they are more restrictive and supplement the requirements of this ordinance.

International Building Code (IBC) 2009 or the latest edition thereof: Secs. 801, 1202, 1403, 1603, 1605, 1612, 3402, and Appendix G.

International Residential Building Code (IRC) 2009 or the latest edition thereof: Secs. R104, R105, R109, R323, Appendix AE101, Appendix E and Appendix J.

### Section 5.04 Development Which May Endanger Human Life

- A. In accordance with the Pennsylvania Flood Plain Management Act, and the regulations adopted by the Department of Community and Economic Development as required by the Act, any new or substantially improved structure which:
  - 1. will be used for the production or storage of any of the following substances listed in Section 5.04.B of this Ordinance; or
  - 2. will be used for any activity requiring the maintenance of a supply of more than 550 gallons, or other comparable volume, of any of the following dangerous materials or substances on the premises; or
  - will involve the production, storage, or use of any amount of radioactive substances:

shall be prohibited in an Identified Floodplain Area. No variance shall be granted.

- B. The following list of materials and substances are considered dangerous to human life and are prohibited in an Identified Floodplain Area:
  - Acetone
  - Ammonia
  - Benzene
  - Calcium carbide
  - Carbon disulfide

- Celluloid
- Chlorine
- Hydrochloric acid
- Hydrocyanic acid
- Magnesium
- Nitric acid and oxides of nitrogen
- Petroleum products (gasoline, fuel oil, etc.)
- Phosphorus
- Potassium
- Sodium
- Sulphur and sulphur products
- Pesticides (including insecticides, fungicides, and rodenticides)
- Radioactive substances, insofar as such substances are not otherwise regulated.

# Section 5.05 Special Requirements for Subdivisions and Land Developments

All subdivision proposals and development proposals in Identified Floodplain A Area (Refer Section 4.02 C) where base flood elevation data are not available, shall be supported by hydrologic and hydraulic engineering analyses that determine base flood elevations and floodway information. The analyses shall be prepared by a licensed professional engineer in a format required by FEMA for a Conditional Letter of Map Revision or Letter of Map Revision. Submittal requirements and processing fees shall be the responsibility of the applicant.

# Section 5.06 Special Requirements for Manufactured Homes

- A. Within any Identified Floodplain Area, manufactured homes shall be prohibited. If a variance is obtained in accordance with criteria in Article VIII, all manufactured homes, and any improvements thereto, shall be:
  - 1. placed on permanent foundation;
  - 2. elevated so that the lowest floor of the manufactured home is at least two and one half (2 ½) feet above base flood elevation;
  - 3. anchored to resist floatation, collapse, or lateral movement; and
  - 4. have all ductwork and utilities including HVAC/heat pump elevated to the Regulatory Flood Elevation.
- B. Installation of manufactured homes shall be done in accordance with the manufacturers' installation instructions as provided by the manufacturer. Where the applicant cannot provide the above information, the requirements of Appendix E of the 2009 "International Residential Building Code" or the "U.S. Department of Housing and Urban Development's Permanent Foundations for Manufactured Housing," 1984 Edition, draft or latest revision thereto and 34 PA Code Chapter 401-405 shall apply.
- C. Consideration shall be given to the installation requirements of the 2009 IBC, and the 2009 IRC or the most recent revisions thereto and 34 PA Code, as amended where appropriate and/or applicable to units where the manufacturers' standards for anchoring cannot be provided or were not established for the proposed unit(s) installation.

# Section 5.07 Special Requirements for Recreational Vehicles

Recreational vehicles in Zones A and AE must either be:

- A. on the site for fewer than 180 consecutive days; or
- B. fully licensed and ready for highway use.

# **ARTICLE VI. PROHIBITED ACTIVITIES**

### Section 6.01 Prohibited Activities

In accordance with the administrative regulations promulgated by the Department of Community and Economic Development to implement the Pennsylvania Flood Plain Management Act, the following activities shall be prohibited within any Identified Floodplain Area:

- A. The commencement of any of the following activities; or the construction, enlargement, or expansion of any structure used, or intended to be used, for any of the following activities:
  - 1. Hospitals
  - 2. nursing homes
  - 3. jails or prisons
- B. The commencement of, or any construction of, a new manufactured home park or manufactured home subdivision, or substantial improvement to an existing manufactured home park or manufactured home subdivision.

#### ARTICLE VII. EXISTING STRUCTURES IN IDENTIFIED FLOODPLAIN AREAS

### Section 7.01 Existing Structures

The provisions of this Ordinance do not require any changes or improvements to be made to lawfully existing structures. However, when an improvement is made to any existing structure, the provisions of Section 7.02 shall apply.

### Section 7.02 Improvements

The following provisions shall apply whenever any improvement is made to an existing structure located within any identified floodplain area;

- A. Any modification, alteration, reconstruction, or improvement, of any kind to an existing structure, to an extent or amount of fifty (50) percent or more of its market value, shall constitute a substantial improvement and shall be undertaken only in full compliance with the provisions of this Ordinance.
- B. The above activity shall also address the requirements of the 35 PA Code, as amended and the 2009 IBC and the 2009 IRC.

- C. Within any Floodway Area/District (Refer Section 4.02 A), no new construction or development shall be allowed, unless the appropriate permit is obtained from the Department of Environmental Protection Regional Office.
- D. Any modification, alteration, reconstruction, or improvement of any kind to an existing structure, in an extent or amount of less than fifty (50) percent of its market value, shall be elevated and/or floodproofed to the greatest extent possible.

#### ARTICLE VIII. VARIANCES

### Section 8.01 General

If compliance with any of the requirements of this Ordinance would result in an exceptional hardship to a prospective builder, developer or landowner, the Board of Supervisors may, upon request, grant relief from the strict application of the requirements.

### Section 8.02 Variance Procedures and Conditions

Requests for variances shall be considered by the Zoning Hearing Board in accordance with the procedures contained in Section 3.12 and the following:

- A. No variance shall be granted for any construction, development, use, or activity within any floodway area that would cause any increase in the BFE. In A Area/District, BFEs are determined using the methodology in Section 4.02 C.
- B. No variance shall be granted for Prohibited Activities (Article VI) or Development Which May Endanger Human Life (Section 5.04).
- C. If granted, a variance shall involve only the least modification necessary to provide relief.
- D. In granting any variance, the Zoning Hearing Board shall attach whatever reasonable conditions and safeguards it considers necessary in order to protect the public health, safety, and welfare, and to achieve the objectives of this Ordinance.
- E In reviewing any request for a variance, the Zoning Hearing Board shall consider, at a minimum, the following:
  - 1. That there is good and sufficient cause.
  - That failure to grant the variance would result in exceptional hardship to the applicant.
  - 3. That the granting of the variance will
    - a. neither result in an unacceptable or prohibited increase in flood heights, additional threats to the public safety, or extraordinary public expense;
    - b. nor create nuisances, cause fraud on, or victimize the public, or conflict with any other applicable state or local ordinances and regulations.
- F. Whenever a variance is granted, Hilltown Township shall notify the applicant in writing that:

- 1. The granting of the variance may result in increased premium rates for flood insurance.
- 2. Such variance may increase the risks to life and property.
- G. A complete record of all variance requests and related actions shall be maintained by the Hilltown Township. In addition, a report of all variances granted during the year shall be included in the annual report to the FEMA.

Notwithstanding any of the above, however, all structures shall be designed and constructed so as to have the capability of resisting the one-percent (1%) annual chance flood.

#### ARTICLE IX DEFINITIONS

# Section 9.01 General

Unless specifically defined below, words and phrases used in this Ordinance shall be interpreted so as to give this Ordinance its most reasonable application.

### Section 9.02 Specific Definitions

ACCESSORY USE OR STRUCTURE – A use or structure on the same lot with, and of a nature customarily incidental and subordinate to, the principle use or structure.

BASE FLOOD - A flood which has a one percent chance of being equaled or exceeded in any given year (also called the "100-year flood" or one-percent (1%) annual chance flood).

BASE FLOOD DISCHARGE - The volume of water resulting from a Base Flood as it passes a given location within a given time, usually expressed in cubic feet per second (cfs).

BASE FLOOD ELEVATION (BFE) - The elevation shown on the Flood Insurance Rate Map (FIRM) for Zones AE, AH, A1-30 that indicates the water surface elevation resulting from a flood that has a 1-percent or greater chance of being equaled or exceeded in any given year.

BASEMENT – Any area of the building having its floor below ground level on all sides.

BUILDING - A combination of materials to form a permanent structure having a roof which is used for the shelter or enclosure of persons, animals or property. Included shall be all manufactured homes and trailers to be used for human habitation.

CONSTRUCTION (NEW) - Structures for which the start of construction commenced on or after March 16, 2015, the effective start date of this floodplain regulation adopted by Hilltown Township and includes any subsequent improvements to such structures. Any construction started after April 15, 1977 and before March 16, 2015, is subject to the Ordinance in effect at the time the permit was issued, provided that start of construction was within 180 days of permit issuance.

DEVELOPMENT - Any man-made change to improved or unimproved real estate, including but not limited to the construction, reconstruction, renovation, repair, expansion, or alteration of buildings or other structures; the placement of manufactured homes; streets, and other paving; utilities; filling, grading and excavation; mining; dredging; drilling operations; storage of equipment or materials; and the subdivision of land.

FLOOD - A temporary inundation by surface water of normally dry land areas.

FLOOD INSURANCE RATE MAP (FIRM) - The official map on which the Federal Emergency Management Agency has delineated both the areas of special flood hazards and the risk premium zones applicable to the community.

FLOOD INSURANCE STUDY (FIS) - The official report provided by the Federal Emergency Management Agency that includes flood profiles, the Flood Insurance Rate Map, the Flood Boundary and Floodway Map, and the water surface elevation of the base flood.

FLOODPLAIN ADMINISTRATOR - Person appointed by the Board of Supervisors to administer and enforce this Ordinance.

FLOODPLAIN AREA (FLOODPLAIN) - A relatively flat or low land area which is subject to partial or complete inundation from an adjoining or nearby stream, river or watercourse; and any area subject to the unusual and rapid accumulation of surface waters from any source.

FLOODPLAIN VIOLATION - The failure of a structure or other development to be fully compliant with the community's flood plain management regulations. A structure or other development without the elevation certificate, other certifications, or other evidence of compliance required in 44 CFR §60.3(b)(5), (c)(4), (c)(10), (d)(3), (e)(2), (e)(4), or (e)(5) is presumed to be in violation until such time as that documentation is provided.

FLOODPROOFING - Any combination of structural and nonstructural additions, changes, or adjustments to structures which reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities, structures and their contents.

FLOODWAY - The channel of a river or other watercourse and adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one foot.

HIGHEST ADJACENT GRADE - The highest natural elevation of the ground surface prior to construction next to the proposed walls of a structure.

#### HISTORIC STRUCTURES – Any structure that is:

- A. Listed individually in the National Register of Historic Places (a listing maintained by the Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register; or
- B. certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district; or
- C. individually listed on a state inventory of historic places in states which have been approved by the Secretary of the Interior; or
- D. Individually listed on a local inventory of historic places that have been certified either:
  - By an approved state program determined by the Secretary of the Interior or

2. Directly by the interior in states without approved programs.

IDENT/FIED FLOODPLAIN AREA – this term is an umbrella term that includes all of the areas within which the community has selected to enforce floodplain regulations. It will always include the area identified as the Special Flood Hazard Area on the Flood Insurance Rate Maps and Flood Insurance Study, and additional areas identified by the Township. Refer Section 4.01 and 4.02 for the specifics on what areas the Township has included in the Identified Floodplain Area.

LOWEST FLOOR - The lowest floor of the lowest fully enclosed area (including basement). An unfinished, flood resistant partially enclosed area, used solely for parking of vehicles, building access, and incidental storage, in an area other than a basement area is not considered the lowest floor of a building, provided that such space is not designed and built so that the structure is in violation of the applicable non-elevation design requirements of this Ordinance.

MOBILE HOME (MANUFACTURED HOME) - A structure, transportable in one or more sections, which is built on a permanent chassis, and is designed for use with or without a permanent foundation when attached to the required utilities. The term includes park trailers, travel trailers, recreational and other similar vehicles which are placed on a site for more than 180 consecutive days.

MANUFACTURED HOME PARK OR SUBDIVISION (NEW) – A manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including at a minimum, the installation of utilities, the construction of streets, and either final site grading for the pouring of concrete pads) is completed on or after the effective date of floodplain management regulations adopted by a community.

MANUFACTURED (MOBILE) HOME PARK OR SUBDIVISION (EXISTING) – A manufactured (mobile) home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured (mobile) homes are to be affixed (including, at a minimum, the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads) is completed before the effective date of the floodplain management regulations adopted by Hilltown Township.

MANUFACTURED HOME PARK OR SUBDIVISION EXPANSION – The preparation of additional sites at an existing manufacture home park or subdivision by the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads).

MINOR REPAIR - The replacement of existing work with equivalent materials for the purpose of its routine maintenance and upkeep, but not including the cutting away of any wall, partition or portion thereof, the removal or cutting of any structural beam or bearing support, or the removal or change of any required means of egress, or rearrangement of parts of a structure affecting the exitway requirements; nor shall minor repairs include addition to, alteration of, replacement or relocation of any standpipe, water supply, sewer, drainage, drain leader, gas, oil, waste, vent, or similar piping, electric wiring or mechanical or other work affecting public health or general safety.

PERSON - An individual, partnership, public or private association or corporation, firm, trust, estate, municipality, governmental unit, public utility or any other legal entity whatsoever, which is recognized by law as the subject of rights and duties.

POST-FIRM STRUCTURE - A structure for which construction or substantial improvement occurred after December 21, 1981 and, as such, would be required to be compliant with the regulations of the National Flood Insurance Program.

PRE-FIRM STRUCTURE - A structure for which construction or substantial improvement occurred on or before December 21, 1981 and, as such, would not be required to be compliant with the regulations of the National Flood Insurance Program.

#### RECREATIONAL VEHICLE - A vehicle which is:

- A. built on a single chassis; and
- B. not more than 400 square feet, measured at the largest horizontal projections; and
- C. designed to be self-propelled or permanently towable by a light-duty truck; and
- D. not designed for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use.

REGULATORY FLOOD ELEVATION - The base flood elevation (BFE) or estimated flood height as determined using simplified methods plus a freeboard safety factor of one and one-half (1  $\frac{1}{2}$ ) feet.

SPECIAL FLOOD HAZARD AREA (SFHA) - An area in the floodplain subject to a 1 percent or greater chance of flooding in any given year. It is shown on the FIRM as Zone A, AO, A1-A30, AE, A99, or, AH.

START OF CONSTRUCTION - Includes substantial improvement and other proposed new development and means the date the Permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition, placement, or other improvement was within 180 days from the date of the permit and shall be completed within twelve (12) months after the date of issuance of the permit unless a time extension is granted, in writing, by the Floodplain Administrator. The actual start means either the first placement of permanent construction of a structure on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufacture home on a foundation. Permanent construction does not include land preparation, such as clearing, grading, and filling; nor does it include the installation of streets and walkways; nor does it include excavation for a basement, footings, piers, or foundations or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. For a substantial improvement, the actual start of construction means the first, alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

STRUCTURE – A walled and roofed building, including a gas or liquid storage tank that is principally above ground, as well as a manufactured home.

STRUCTURE, ACCESSORY - Refer Use, Accessory.

STRUCTURE (EXISTING) – A structure for which the "start of construction" commenced before the effective date of the FIRM or before January 1, 1975 for FiRMs effective before that date. "Existing structure" may also be referred to as "existing construction".

SUBDIVISION - The division or redivision of a lot, tract, or parcel of land by any means into two or more lots, tracts, parcels or other divisions of land including changes in existing lot lines for the purpose, whether immediate or future, of lease, partition by the court for distribution to heirs, or devisees, transfer of ownership or building or lot development.

SUBSTANTIAL DAMAGE - Damage from any cause sustained by a structure whereby the cost of restoring the structure to its before-damaged condition would equal or exceed fifty (50) percent or more of the market value of the structure before the damage occurred.

SUBSTANTIAL IMPROVEMENT - Any reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds fifty (50) percent of the market value of the structure before the "start of construction" of the improvement. This term includes structures which have incurred "substantial damage" regardless of the actual repair work performed. The term does not, however, include any project for improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been identified by the local code enforcement official and which are the minimum necessary to assure safe living conditions.

UNIFORM CONSTRUCTION CODE (UCC) – The statewide building code adopted by The Pennsylvania General Assembly in 1999 applicable to new construction in all municipalities whether administered by the municipality, a third party or the Department of Labor and Industry. Applicable to residential and commercial buildings, The Code adopted The International Residential Code (IRC) and the International Building Code (IBC), by reference, as the construction standard applicable with the State floodplain construction. For coordination purposes, references to the above are made specifically to various sections of the IRC and the IBC.

USE, ACCESSORY OR STRUCTURE - A use or structure located on the same lot with, and of a nature customarily incidental and subordinate to, a principal use or structure and clearly incidental or subordinate to, and in connection with, the principal use or structure.

VARIANCE – A grant of relief by the Hilltown Township Zoning Hearing Board from the terms of a floodplain management regulation.

VIOLATION – The failure of a structure or other development to be fully compliant with the community's flood plain management regulations. A structure or other development without the elevation certificate, other certifications, or other evidence of compliance required in 44 CFR  $\S60.3(b)(5)$ , (c)(4), (c)(10), (d)(3), (c)(2), (e)(4), or (e)(5) is presumed to be in violation until such time as that documentation is provided.

# Section 10.01 Repealer

Any Ordinance or Ordinance provision of the municipality inconsistent with any of the provisions of this Ordinance is hereby repealed to the extent of the inconsistency only.

ENACTED and ORDAINED at a regular meeting of the Hilltown Township Board of Supervisors on the do the day of March 16, 2015. This Ordinance shall take effect on March 16, 2015.

Attest:

Richard C. Schnaedter, Township Manager

John B. McIlhinney, Chairman

Kenneth B. Bennington. Vice Chairman

James C. Groff, Member